



Westinghouse

INNOVATION YOU CAN BE SURE OF

iGen1200

Digital Inverter Generator

Westinghouse digital inverter generators offer you the ultimate in portable power convenience. Lightweight, fuel efficient and quiet, their mains-quality electrical output can safely power all of your sensitive electronic equipment. They're an essential part of your gear for caravanning and camping and also great for home as a backup power supply.

Features and Benefits

Powerful

1,200 Watts maximum output is the highest in its class to run more of your electrical devices.

Lightweight

At only 15 kg it can be easily carried by one person using the ergonomic non-slip handle.

Quiet

Ultra-silent running from only 51 dB(A) that won't disturb you or your neighbours.

Long Running

Up to 15 hours achieved by its fuel-efficient engine and biggest-in-class 2.8 L fuel tank.

Easy To Use

Yellow-coloured touch points guide you to the controls required for normal operation.

Mains Quality Electricity

Digital inverter technology safely powers all of your sensitive electronic equipment.

Clean Air Technology

4-stroke OHV petrol engine with Australian and US EPA compliant emission controls.

Plug and Play

Everything you need is in the box. No assembly required. Just add petrol.

Safety Protection

Electrical overload circuit breaker and low engine oil shutdown safeguards.

Warranty Protection

2-year domestic use warranty to safeguard your investment (conditions apply).

1000/1200

RUNNING WATTS STARTING WATTS



PURE SINE WAVE

Control Panel Functions



Power - when you need it - where you need it

Specifications

iGen1200

ENGINE		240 VOLT AC ELECTRICAL	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	Voltage (V)	240
Displacement (cc)	54	Frequency (Hz)	50
Maximum Speed (rpm)	5,200	Number of Phases	1
Oil Capacity (mL)	250	Continuous Running Power (W) *	1,000
Low Oil Shutdown	Yes	Maximum Starting Power (W)	1,200
Spark Plug	Torch A5RTC	Continuous Running Current (A)	4.2
Fuel	Unleaded Petrol	Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Fuel Tank Capacity (L)	2.8	Total Harmonic Distortion (THD)	< 2.5%
Fuel Gauge	No	Receptacle	15 A, IP44
Auto-Speed ECO Throttle	Yes	Overload Protection	Electronic
Starting Method	Recoil	Alternator	Brushless, Permanent Magnet
Hour Meter	Yes	Output Indicator Light	Yes
Run Time @ 225 / 900 W	9 / 4.5 hours	12 VOLT DC ELECTRICAL	
Noise Level @ 225 / 900 W	52 / 58 dB(A) @ 7m	Voltage (V)	12
DIMENSIONS		Maximum Current (A)	5
Length (mm)	463	Maximum Power (W)	60
Width (mm)	262	Receptacle	5 A, IP44
Height (mm)	395	5 VOLT DC ELECTRICAL	
WEIGHT		Voltage (V)	5
Weight - Dry (kg)	15	Maximum Current (A)	2.1
Weight - Wet (kg)	17	Maximum Power (W)	10
		Receptacle	USB Type A, IP44

* Rated output at 1.0 power factor.



Westinghouse

INNOVATION YOU CAN BE SURE OF

westinghouseoutdoorpower.com.au

Specifications are subject to change without notice.

2019-09-16